


THE SUFFOLK FENCE: 50x8mm 2000mm LONG ±45mm TO BE DRIVEN INTO GROUND 800MM FOR A 1200MM NOMINAL FENCE HEIGHT AT 1M NOMINAL POST SPACING

5off 16mm SOLID ROUND RAILS

POSTS AND RAILS SUPPLIED LOOSE TO BE WELDED ON SITE TO ENSURE FOLLOWING OF GROUND CONTOURS

 <b>WENHAM YOUNG</b> <small>ESTD 1954 ENGLAND</small> <b>Wenham Young Limited,</b> <b>Burnbank House, Church Lane</b> <b>Witnesham, Ipswich</b> <b>Suffolk, IP6 9JD</b> <b>Tel: 07734439652</b>	UNLESS OTHERWISE SPECIFIED: DIMENSIONS ARE IN MILLIMETERS TOLERANCES: X: ±2.5      X.XX: ±0.13 X.X: ±0.25    X.XXX: ±0.013		CUSTOMER: <b>Wenham Young</b>	
	MATERIAL: Plain Carbon Steel		DESCRIPTION: <b>The Suffolk Post (50x8)</b>	
FINISH: Hot Rolled WEIGHT: 63158.62 Kg		BY: TY DATE: 16/01/2024	DWG NO: <b>000-001-0002</b>	
DEBUR AND BREAK SHARP EDGES DO NOT SCALE DRAWING <b>IF IN DOUBT ASK!</b>		CHECKED: APPROVED:	SHEET SCALE: 1:20 SHEET SIZE: A3 SHEET NUMBER: 1 OF 1	REV: